

astm d2922

Understanding ASTM D2922: The Standard Test Method for Rubber Property–Resilience (Rebound)

ASTM D2922 is a widely recognized and authoritative standard developed by ASTM International that specifies the procedure for determining the resilience, or rebound, of rubber materials. This test method plays a crucial role in evaluating the elastic properties of rubber compounds, which are fundamental in industries such as automotive, aerospace, manufacturing, and consumer products. By providing a consistent and standardized approach to measure rubber resilience, ASTM D2922 ensures that manufacturers and researchers can accurately assess material performance, compare results across different batches or suppliers, and meet quality assurance requirements.

In this comprehensive guide, we will explore the purpose and scope of ASTM D2922, detail the testing procedure, discuss its significance, and highlight best practices to ensure accurate and reliable results.

What Is ASTM D2922?

ASTM D2922 is a standardized test method designed to measure the resilience of rubber materials by quantifying their ability to recover energy after deformation. Resilience, in this context, refers to the material's capacity to absorb energy during compression or deformation and then recover that energy upon release. The rebound value obtained from this test reflects the elastic nature of the rubber and is critical for applications where shock absorption and energy return are vital.

The test is primarily used for:

- Quality control of rubber products
- Material characterization in research and development
- Comparing different rubber formulations
- Ensuring compliance with industry standards and specifications

Scope and Applications of ASTM D2922

ASTM D2922 applies to rubber materials in various forms, including sheets, molded parts, and extruded products. The method is suitable for testing vulcanized and unvulcanized rubber but is most commonly used for vulcanized

rubber compounds.

Applications include:

- Automotive tires and suspension components
- Mechanical seals and gaskets
- Vibration isolators and shock absorbers
- Athletic and sports equipment
- Consumer rubber goods such as footwear and rubber mats

The test provides a numerical rebound value (expressed as a percentage), which correlates with the material's elastic properties and can be used to predict performance under dynamic loading conditions.

Principle of the Test Method

The core principle of ASTM D2922 involves dropping a steel ball or a specified impact device onto a rubber specimen and measuring the height of the rebound. The ratio of the rebound height to the initial drop height is calculated as the resilience or rebound percentage.

This process involves:

1. Dropping an impactor from a predetermined height onto the rubber specimen.
2. Measuring the height to which the impactor bounces back after impact.
3. Calculating the rebound resilience as a percentage of the initial drop height.

The higher the rebound percentage, the more elastic the rubber material is considered to be.

Detailed Testing Procedure

To ensure the accuracy and consistency of ASTM D2922 results, adherence to the detailed testing steps is essential.

1. Sample Preparation

- Prepare specimens according to the specified dimensions, typically rectangular or cylindrical samples.
- Condition samples at a standard atmosphere ($23^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and $50\% \pm 10\%$ relative humidity) for at least 24 hours prior to testing.
- Ensure surfaces are clean, dry, and free from any contaminants or surface defects.

2. Equipment Setup

- Use a rebound tester or impact device calibrated as per the standard.
- The impactor should be a steel ball or a specified weight and size, depending on the test requirements.
- Set the initial drop height as specified; common heights range from 300 mm to 500 mm.

3. Conducting the Test

- Position the specimen securely on the testing platform.
- Release the impactor from the predetermined height, allowing it to strike the specimen.
- Measure the height of the rebound using a suitable measuring device, such as a graduated scale or laser measurement system.
- Record the rebound height.

4. Calculations

- Calculate the resilience percentage using the formula:

$$\text{Resilience (\%)} = (\text{Rebound Height} / \text{Drop Height}) \times 100$$

- Repeat the test at least 3 times for each specimen to ensure reproducibility.
- Average the results to obtain a representative rebound value.

Factors Influencing Test Results

Several factors can affect the accuracy and consistency of ASTM D2922 test results:

- Specimen Condition: Proper conditioning in controlled environments is critical.
- Impactor Calibration: Regular calibration ensures consistent impact energy.
- Drop Height: Strict adherence to specified heights avoids variability.
- Surface Area and Thickness: Variations can influence rebound behavior.
- Temperature and Humidity: Environmental conditions directly impact rubber elasticity.

Significance and Interpretation of Results

The rebound resilience measured via ASTM D2922 provides insights into the elastic characteristics of rubber materials. High rebound values indicate a material with strong elastic recovery, suitable for applications demanding shock absorption and energy return. Conversely, lower rebound values suggest a more damping or less elastic material.

Typical rebound ranges:

- Natural rubber: 50-70%
- Synthetic rubbers (e.g., SBR, EPDM): 40-60%
- Vulcanized rubber used in tires: 50-65%

Applications of Results:

- Material selection for specific applications.
- Quality control during manufacturing.
- Monitoring material aging or degradation.
- Comparing different formulations or batches.

Advantages and Limitations of ASTM D2922

Advantages

- Provides a quick and straightforward assessment of rubber elasticity.
- Highly reproducible when proper procedures are followed.
- Suitable for routine quality control.
- Non-destructive for small samples.

Limitations

- Does not account for hysteresis or damping behavior comprehensively.
- Sensitive to surface conditions and specimen preparation.
- Results can vary with temperature and environmental conditions if not controlled.
- Not suitable for very soft or highly compliant rubber materials.

Best Practices for Accurate ASTM D2922 Testing

- Always condition specimens as per ASTM standards before testing.
- Calibrate impact devices regularly.
- Maintain a consistent testing environment.

- Use specimens with uniform dimensions and surface finish.
- Conduct multiple tests and average the results.
- Document all test parameters meticulously.

Conclusion

ASTM D2922 is an essential standard for evaluating the resilience of rubber materials, providing valuable data that influence product design, quality assurance, and material development. Its straightforward methodology, when correctly applied, offers reliable insights into the elastic recovery behavior of rubber compounds, helping manufacturers meet performance specifications and industry standards.

By understanding the principles, procedures, and factors affecting ASTM D2922 tests, engineers and quality control specialists can ensure accurate assessments of rubber resilience, ultimately leading to better-performing products and enhanced customer satisfaction. Whether for research purposes or routine quality checks, ASTM D2922 remains a cornerstone in the field of rubber testing and material characterization.

Keywords: ASTM D2922, rubber resilience, rebound test, rubber properties, material testing, ASTM standards, impact testing, rubber elasticity, quality control rubber

Frequently Asked Questions

What is ASTM D2922 and what does it specify?

ASTM D2922 is a standard test method that specifies the procedure for determining the viscosity of lubricating oils and related products using a rotating cylinder viscometer at specified temperatures.

Why is ASTM D2922 important for lubricating oil analysis?

ASTM D2922 provides a reliable and standardized way to measure viscosity, which is critical for evaluating oil performance, ensuring proper engine and machinery operation, and meeting quality specifications.

What equipment is required to perform ASTM D2922 testing?

The test requires a rotating cylinder viscometer, a temperature control bath, and related accessories such as thermometers and sample containers to ensure accurate viscosity measurements at specified temperatures.

How does temperature influence the results obtained from ASTM D2922?

Viscosity measurements are highly temperature-dependent; ASTM D2922 specifies testing at particular temperatures (e.g., 40°C and 100°C) to ensure consistency and comparability of results across different samples and laboratories.

Are there any recent updates or modifications to ASTM D2922?

As of October 2023, ASTM D2922 remains a standard method; however, laboratories should verify with ASTM updates or revisions to ensure compliance with the latest testing procedures and specifications.

Additional Resources

ASTM D2922: An In-Depth Review of the Standard Test Method for Determining Flash Point by Tag Closed Tester

Understanding the behavior of petroleum products and other combustible liquids is essential for safety, quality control, and regulatory compliance within various industries such as petroleum refining, transportation, storage, and manufacturing. One of the most critical parameters in evaluating these materials is their flash point—the lowest temperature at which a liquid produces enough vapor to ignite in the presence of an ignition source. ASTM D2922 provides a standardized, reliable method for determining the flash point of petroleum products using the Tag Closed Tester. This review offers a comprehensive examination of ASTM D2922, exploring its purpose, methodology, advantages, limitations, and practical applications.

Overview of ASTM D2922

ASTM D2922 is a widely adopted standard developed by ASTM International, designed to establish a consistent procedure for measuring the flash point of petroleum products and other combustible liquids. The method employs the Tag Closed Tester, a device that allows for safe testing by preventing vapor loss and minimizing exposure to ignition sources during the measurement process.

The primary goal of ASTM D2922 is to provide a repeatable, accurate, and reproducible technique to determine the flash point, which is vital for safety data sheets, regulatory compliance, and product classification. It is particularly suited for liquids with flash points above approximately 37.8°C (100°F), although it can be used across a broad temperature range for various

liquids.

Historical Context and Significance

Since its initial development, ASTM D2922 has become a cornerstone method for flash point determination, especially for petroleum-based products. Its significance lies in the standardization it offers, ensuring that measurements are consistent regardless of the laboratory or technician conducting the test. This consistency is critical when comparing products, verifying compliance with safety standards, or conducting quality assurance.

The method's design emphasizes safety, efficiency, and accuracy, making it a preferred choice for laboratories and industries worldwide. Its widespread adoption underscores its reliability and the importance of standardized testing in managing fire and explosion hazards associated with combustible liquids.

Detailed Methodology

Principle of the Test

ASTM D2922 involves gradually heating a sample of the liquid in a closed, sealed container, while intermittently applying a small ignition source to the vapor above the liquid. The temperature at which a brief flash of fire occurs—indicating vapor ignition—is recorded as the flash point.

The key features of the Tag Closed Tester include a metal cup with a lid, a heating mantle or bath, a thermometer, and a spark igniter. The closed nature of the system reduces vapor loss, providing more accurate and consistent measurements.

Step-by-Step Procedure

1. Sample Preparation:

- A representative sample of the liquid is placed into the metal cup of the Tag Closed Tester, typically about 30 mL.
- The sample must be at a specified temperature, often room temperature, before testing.

2. Assembly and Heating:

- The cup is sealed with the lid, which contains a small opening for the ignition source and a thermometer port.
- The assembly is immersed in a heating bath, and the temperature is gradually increased at a controlled rate, generally 5°C per minute.

3. Application of Ignition Source:

- At regular intervals, the operator introduces a small spark near the vapor space.
- If a flash occurs, the temperature is recorded as the flash point.
- If no flash occurs, heating continues until a flash is observed or a predetermined maximum temperature is reached.

4. Repeatability and Recordkeeping:

- The test is usually performed multiple times to ensure consistency.
- The lowest temperature at which a flash is observed is recorded as the flash point.

5. Data Interpretation:

- The flash point is reported based on the observed flashes, considering repeatability and operator judgment.

Features and Characteristics of ASTM D2922

Advantages:

- **Safety:** The closed tester minimizes vapor escape and reduces explosion risk during testing.
- **Standardization:** Provides a uniform procedure recognized internationally.
- **Applicability:** Suitable for a broad range of liquids with varying flash points.
- **Repeatability and Reproducibility:** Designed to produce consistent results across different laboratories.
- **Automation Compatibility:** The method can be adapted for automated systems, increasing throughput.

Limitations:

- **Sample Types:** Less effective for highly volatile liquids with flash points below 37.8°C, which are better tested by open cup methods.
- **Maximum Temperature:** Typically limited to a certain temperature range, possibly requiring alternative methods for very high flash points.
- **Operator Skill:** Accurate detection of the flash point depends on operator judgment in observing flashes.
- **Equipment Cost:** The Tag Closed Tester apparatus can be more expensive than open cup equivalents.

Key Features Summary:

Feature	Description
Method Type	Closed cup, ignition source application at intervals
Temperature Range	Generally suitable for liquids with flash points above 37.8°C
Safety Mechanism	Closed system reduces vapor release and explosion risk
Standardization	Based on ASTM D2922, recognized globally
Automation	Compatible with automated testing setups

Applications and Industry Relevance

ASTM D2922 is extensively employed across various sectors:

- Petroleum Industry: For quality control of fuels, lubricants, and oils, ensuring safety thresholds are met.
- Chemical Manufacturing: To evaluate flammable solvents and chemicals.
- Transportation and Storage: To classify liquids according to their flash point, influencing handling and storage regulations.
- Regulatory Compliance: Many safety standards and regulations reference ASTM D2922 as the method of choice for flash point determination.
- Research and Development: For product formulation and safety testing.

Comparative Analysis with Other Flash Point Tests

While ASTM D2922 is a widely accepted method, it is often compared with other standards, such as:

- ASTM D93 (Pensky-Martens Closed Cup): Suitable for lower flash point liquids.
- ASTM D56 (Open Cup): Used for quick screening but less accurate and less safe due to vapor release.
- IP 34 (British Standard): Similar to ASTM D92 but with slight procedural differences.

Pros of ASTM D2922 over Open Cup Methods:

- Safer due to closed system
- Less vapor loss, leading to more accurate measurements

- Better suited for liquids with higher flash points

Cons:

- Slightly longer testing time
- More complex equipment setup

Operational Considerations and Best Practices

To ensure accurate and consistent results when using ASTM D2922:

- Calibration: Regular calibration of thermometers and ignition sources is essential.
- Sample Homogeneity: Ensure samples are well-mixed and free of impurities or sediments.
- Controlled Heating Rate: Maintain the recommended heating rate to avoid overshooting the flash point.
- Operator Training: Skilled personnel should be trained to observe flashes accurately.
- Replicate Tests: Conduct multiple runs to confirm results and account for variability.

Conclusion

ASTM D2922 stands out as a robust, safe, and standardized method for determining the flash point of petroleum products and other combustible liquids. Its closed cup design enhances safety and measurement reliability, making it indispensable in industries where fire safety and regulatory compliance are paramount. While it has some limitations—such as unsuitability for very low flash point liquids—it remains a go-to method for a broad spectrum of applications.

By understanding its methodology, features, and practical considerations, laboratories and industry professionals can leverage ASTM D2922 effectively, ensuring accurate safety assessments and regulatory adherence. Continued advancements in automation and instrumentation are likely to further enhance its utility, maintaining its relevance in the evolving landscape of safety testing.

In summary:

- ASTM D2922 provides a standardized, safe, and reliable method for flash point determination.
- Its closed cup design minimizes vapor loss and enhances safety.
- Suitable for a wide range of petroleum products with moderate to high flash points.
- Requires skilled operation and calibration for best results.
- Remains a critical tool in quality control, safety, and regulatory compliance across various industries.

Final Thoughts

As safety standards become increasingly stringent and the demand for precise data grows, ASTM D2922's role in the testing of combustible liquids will continue to be vital. Its balance of safety, accuracy, and standardization makes it an essential method in the arsenal of laboratory testing techniques for industry professionals worldwide.

[Astm D2922](#)

astm d2922: Geotechnical Investigation Methods Roy E. Hunt, 2006-10-31 The investigation phase is the most important segment of any geotechnical study. Using the correct methods and properly interpreting the results are critical to a successful investigation. Comprising chapters from the second edition of the revered Geotechnical Engineering Investigation Handbook, Geotechnical Investigation Methods offers clear, conc

astm d2922: Design and Construction of RCRA/CERCLA Final Covers United States. Environmental Protection Agency, 1991

astm d2922: Geotechnical Ground Investigation Myint Win Bo, 2022-03-18 Geotechnical investigation, which is usually implemented to obtain baseline information of ground and groundwater, is the focus of this book. Authored by practitioner and academic who is extensively involved in geotechnical ground investigations over four continents, this book covers both large scale preliminary ground investigation and intrusive detailed investigation, as well as specialized in-situ testing to obtain advanced geotechnical parameters of soils. Both surface and borehole geophysical methods used in geotechnical investigation, including methods of sampling and tools to obtain good quality soil samples are also discussed and presented in the book. Written for advanced undergraduate and graduate students, researchers and practitioners in the fields of geotechnical engineering, geoenvironmental engineering, and ground investigation, the book also provides guidelines on presenting factual geotechnical data and preparing factual reports. Related Link(s)

astm d2922: Guide to Technical Resources for the Design of Land Disposal Facilities , 1989

astm d2922: Geotechnical Engineering Investigation Handbook Roy E. Hunt, 2005-04-12 The Geotechnical Engineering Investigation Handbook provides the tools necessary for fusing geological characterization and investigation with critical analysis for obtaining engineering design criteria. The second edition updates this pioneering reference for the 21st century, including developments that have occurred in the twen

astm d2922: NIST Special Publication , 2002

astm d2922: An Index of U.S. Voluntary Engineering Standards, Supplement 1 William J. Slattery, 1972

astm d2922: NBS Special Publication , 1977

astm d2922: An Index of U.S. Voluntary Engineering Standards. Supplement William J. Slattery, 1972

astm d2922: Training and Reference Manual for Special Inspectors Houman John Parsaie, 2001-10-24 This manual has been prepared for use as a reference materials for their day to day inspection business and for assistance in the training of new inspectors. This is also a supplement to applicable Standards, such as ASTM, ACI, AWS, etc. as well as building codes, such as UBC, SBC, etc.; thus, any references made in this manual reflects to the applicable code and/or standard test method. Inspection is the observation of construction for conformance with the approved design documents. It shall not be relied upon by others as guarantee or acceptance of work, nor shall it in any manner relieve any contractor or other party from their obligations and responsibilities under the construction contract, or generally accepted industry custom, or building codes and standards. Included in this manual are materials for other testing and inspection, for which there are currently no special training program or certifications available or offered. H. John Parsaie, Ph.D. Seattle, Washington

astm d2922: Geoenvironmental Engineering Hari D. Sharma, Krishna R. Reddy, 2004-05-20 Geoenvironmental Engineering covers the application of basic geological and hydrological science, including soil and rock mechanics and groundwater hydrology, to any number of different environmental problems. * Includes end-of-chapter summaries, design examples and worked-out numerical problems, and problem questions. * Offers thorough coverage of the role of geotechnical engineering in a wide variety of environmental issues. * Addresses such issues as remediation of in-situ hazardous waste, the monitoring and control of groundwater pollution, and the creation and management of landfills and other above-ground and in-situ waste containment systems.

astm d2922: Stabilization/solidification of CERCLA and RCRA Wastes , 1989

astm d2922: Waste Treatment in the Metal Manufacturing, Forming, Coating, and Finishing Industries Lawrence K. Wang, Nazih K. Shammass, Yung-Tse Hung, 2016-04-19 Comprehensive in its scope and directly applicable to daily waste management problems of specific industries, Waste Treatment in the Metal Manufacturing, Forming, Coating, and Finishing Industries covers hazardous industrial waste treatment, renovation, and reuse in the metal manufacturing, forming, coating, enameling, and finishing industries. It

astm d2922: *Zortman and Landusky Mines Reclamation Plan Modifications and Mine Life Extensions* , 1996

astm d2922: *Description and Sampling of Contaminated Soils* J. Russell Boulding, 2017-09-29 This second edition of EPA's bestselling book, Description and Sampling of Contaminated Soils: A Field Guide, Second Edition, has been revised and significantly expanded over the original edition. An ideal reference for anyone involved in site investigations, this guide describes how to determine the amount and extent of soil contamination and potential for movement of contaminants in the soil and groundwater. It contains checklists, tables, and step-by-step descriptions of methods and procedures for: Cost-effective, detailed site investigations for evaluating the potential for contaminant transport Field collection of information on soil engineering properties required for remediation selection and design This guide also features an adaptation of soil description procedures used by the U.S. Soil Conservation Service (SCS) for investigating contaminated sites. The SCS soil description and classification procedures, when used in combination with the Unified Soil Classification System currently used by geologists and engineers, greatly improves contaminated site assessments.

astm d2922: Index of U.S. Nuclear Standards William J. Slattery, 1977

astm d2922: *Index of Specifications and Standards* , 2005

astm d2922: 1990 Directory of NVLAP Accredited Laboratories Nancy M. Trahey, 1990

astm d2922: Design and Construction Issues at Hazardous Waste Sites , 1991

astm d2922: *Immobilization Technology Seminar* Center for Environmental Research Information (U.S.), 1989

Related to astm d2922

ASTM International | ASTM Over 13,000 ASTM standards operate globally. Defined and set by us, they improve the lives of millions every day. ASTM provides the standards and solutions you need to achieve the

ASTM International - Wikipedia ASTM International, formerly known as American Society for Testing and Materials, is a standards organization that develops and publishes voluntary consensus technical international

ASTM International - ANSI Webstore ASTM International, founded as the American Society for Testing and Materials, is a nonprofit organization that develops and publishes approximately 12,000 technical standards, covering

Standards & Publications | ASTM Our extensive catalog is your source for standards from ASTM and other leading standards developers, plus thousands of journal articles, manuals, and technical papers dating back over

What are ASTM Standards? Full Form, Types, and Uses in Industries ASTM full form is American Society for Testing and Materials, which develops and publishes international standards for a wide range of materials, products, and services

About ASTM Overview About ASTM Overview Over 13,000 ASTM standards operate globally. Defined and set by us, they improve the lives of millions every day. Combined with our innovative business services,

ASTM Fact Sheet - Overview - About Us What Is ASTM? Formed in 1898, ASTM International is one of the world's largest international standards developing organizations. Defined and set by us, ASTM standards improve the lives

ASTM Standards - Applied Testing & Geosciences ASTM International, formerly known as the American Society for Testing and Materials, is a globally recognized organization that develops and publishes technical standards for materials,

Standards & Solutions | ASTM More than 13,000 ASTM standards are used worldwide to improve product quality, enhance safety, and facilitate trade. Organized in 80+ volumes, ASTM standards are available

List of ASTM Standards | Available Online or PDF With our online standards platform ASTM Compass®, you can gain access to any of the over 12,000+ ASTM standards listed below, as well as standards from other international

ASTM International | ASTM Over 13,000 ASTM standards operate globally. Defined and set by us, they improve the lives of millions every day. ASTM provides the standards and solutions you need to achieve the

ASTM International - Wikipedia ASTM International, formerly known as American Society for Testing and Materials, is a standards organization that develops and publishes voluntary consensus technical international

ASTM International - ANSI Webstore ASTM International, founded as the American Society for Testing and Materials, is a nonprofit organization that develops and publishes approximately 12,000 technical standards, covering

Standards & Publications | ASTM Our extensive catalog is your source for standards from ASTM and other leading standards developers, plus thousands of journal articles, manuals, and technical papers dating back over

What are ASTM Standards? Full Form, Types, and Uses in Industries ASTM full form is American Society for Testing and Materials, which develops and publishes international standards for a wide range of materials, products, and services

About ASTM Overview About ASTM Overview Over 13,000 ASTM standards operate globally. Defined and set by us, they improve the lives of millions every day. Combined with our innovative business services,

ASTM Fact Sheet - Overview - About Us What Is ASTM? Formed in 1898, ASTM International is

one of the world's largest international standards developing organizations. Defined and set by us, ASTM standards improve the lives

ASTM Standards - Applied Testing & Geosciences ASTM International, formerly known as the American Society for Testing and Materials, is a globally recognized organization that develops and publishes technical standards for

Standards & Solutions | ASTM More than 13,000 ASTM standards are used worldwide to improve product quality, enhance safety, and facilitate trade. Organized in 80+ volumes, ASTM standards are available

List of ASTM Standards | Available Online or PDF With our online standards platform ASTM Compass®, you can gain access to any of the over 12,000+ ASTM standards listed below, as well as standards from other international

Related Articles

- [johns model reflection](#)
- [em coding cheat sheet](#)
- [programming language pragmatics pdf](#)

[Back to Home](#)