

astm c42

ASTM C42: A Comprehensive Guide to Its Standards and Applications

When it comes to the quality control and standardization of aggregate materials used in construction, ASTM C42 plays a pivotal role. Established by the American Society for Testing and Materials (ASTM), this specification outlines the procedures for testing and evaluating fine and coarse aggregates used in concrete and other building applications. Understanding ASTM C42 is essential for engineers, contractors, and quality assurance professionals seeking to ensure compliance with industry standards and achieve durable, safe, and high-quality construction projects.

What is ASTM C42?

ASTM C42 refers to the "Standard Test Method for Particle-Size Distribution (Gradation) of Fine and Coarse Aggregates." This standard provides a systematic approach to determine the particle size distribution of aggregates, which is a critical factor influencing concrete workability, strength, and durability.

By adhering to ASTM C42, professionals can verify that their aggregates meet specific gradation requirements, ensuring consistency across batches and compatibility with the intended concrete mix design. This standard also facilitates comparison between different sources of aggregates and helps identify variations that could impact the performance of construction materials.

Scope and Purpose of ASTM C42

Primary Objectives

- To establish standardized procedures for testing the particle size distribution of aggregates.
- To ensure aggregates meet specified gradation requirements for concrete and other construction applications.
- To provide a basis for quality assurance and control in aggregate

production and procurement.

Applications of ASTM C42

- Designing concrete mixes with specific workability and strength characteristics.
- Assessing the consistency and quality of aggregate sources.
- Compliance testing for construction projects requiring adherence to ASTM standards.
- Research and development in aggregate processing and material science.

Key Components of ASTM C42 Testing Procedures

The ASTM C42 standard specifies several critical steps to accurately determine the gradation of aggregate materials.

Sample Preparation

- Collect representative samples from the aggregate batch.
- Dry the sample to a consistent moisture content to prevent measurement inaccuracies.
- Mix the sample thoroughly to ensure uniformity before testing.

Sieving Process

- Use a set of standard sieves with specified opening sizes, typically ranging from coarse (e.g., 4 inches) to fine (e.g., No. 200).
- Operate the mechanical sieve shaker for a prescribed duration to ensure consistent agitation.

- Weigh the amount of material retained on each sieve accurately.

Calculating Gradation

- Determine the percentage of material retained on each sieve relative to the total sample weight.
- Plot the particle size distribution curve based on the cumulative passing and retained percentages.
- Compare the results to the gradation requirements specified in project documents or standards.

Importance of Particle Size Distribution in Construction

Understanding the gradation of aggregates is vital because it directly affects various properties of concrete and other building materials.

Workability

Well-graded aggregates with a proper distribution of particle sizes improve the workability of concrete, making it easier to place and finish.

Strength and Durability

Appropriate gradation ensures optimal packing density, reducing the voids between particles, which enhances strength and minimizes permeability, thereby increasing durability.

Economical Use of Cement

Proper aggregate gradation reduces the amount of cement required to achieve desired strength, leading to cost savings and environmental benefits.

Standards and Specifications Related to ASTM C42

While ASTM C42 provides the testing methodology, other standards specify acceptable gradation ranges for different types of concrete and construction requirements.

Common Gradation Limits

- Fine aggregates (sand) typically conform to gradation limits outlined in ASTM C33.
- Coarse aggregates have specific size ranges, often governed by project specifications or standards like AASHTO M 43.

Quality Control and Certification

- Manufacturers and suppliers often perform ASTM C42 testing as part of their quality assurance programs.
- Results from ASTM C42 tests can be included in material certification documents to verify compliance.

Benefits of Using ASTM C42 in Construction Projects

Adopting ASTM C42 testing procedures offers numerous advantages that contribute to the overall success of construction projects.

Ensures Consistency

Regular testing helps maintain consistent aggregate quality across different batches and sources, reducing variability in concrete properties.

Facilitates Compliance

Meeting ASTM standards is often a contractual requirement, and proper testing ensures projects remain compliant with industry regulations.

Enhances Durability and Performance

Accurate gradation analysis leads to better concrete mixes, ultimately resulting in structures that are more durable and have longer service lives.

Supports Sustainable Construction

Optimized aggregate gradation reduces cement usage and minimizes waste, contributing to environmentally sustainable practices.

Implementing ASTM C42 Testing: Best Practices

For effective and accurate results, professionals should follow best practices when conducting ASTM C42 tests.

Proper Equipment Maintenance

- Ensure sieves are clean and undamaged.
- Use calibrated scales for accurate weight measurements.
- Operate sieve shakers according to manufacturer instructions.

Representative Sampling

- Collect samples from multiple points within a batch to capture variability.
- Follow standardized procedures for sample size and handling.

Accurate Data Recording and Analysis

- Document all measurement data meticulously.
- Use proper plotting techniques for gradation curves.
- Compare results with relevant specifications to assess compliance.

Conclusion

ASTM C42 is a cornerstone standard in the field of aggregate testing, ensuring that the materials used in concrete and construction meet strict quality and performance criteria. By understanding and implementing ASTM C42 testing procedures, industry professionals can improve project outcomes, enhance structural integrity, and promote sustainable building practices. Whether you're a supplier, engineer, or contractor, incorporating ASTM C42 into your quality assurance protocols is essential for achieving consistent, reliable, and compliant construction results.

If you're seeking reliable aggregate testing services or need assistance with ASTM C42 compliance, partnering with experienced laboratories and testing professionals can streamline your process and ensure your materials meet all necessary standards.

Frequently Asked Questions

What is ASTM C42 and what does it test for?

ASTM C42 is a standard test method used to determine the particle size distribution of fine aggregate (sand) used in concrete and other construction applications.

Why is ASTM C42 important in construction materials testing?

ASTM C42 ensures that the fine aggregate meets specific size distribution requirements, which affects the workability, strength, and durability of concrete and mortar mixes.

What equipment is required to perform ASTM C42 testing?

The test requires a sieve shaker, a set of standard sieves with specified mesh sizes, a sample of fine aggregate, and a balance to weigh the fractions.

How is the ASTM C42 test conducted?

A representative sample of fine aggregate is sieved through a stack of standard sieves, shaken for a specified period, and then the weight of material retained on each sieve is measured to determine the particle size distribution.

What are the typical size fractions analyzed in ASTM C42?

ASTM C42 typically analyzes particle sizes ranging from 4.75 mm (No. 4 sieve) down to 75 microns (No. 200 sieve).

How does the results of ASTM C42 influence concrete mix design?

The particle size distribution data helps determine the proper proportions of fine aggregate, ensuring optimal workability, compaction, and strength of the concrete.

What are common issues when performing ASTM C42 testing?

Common issues include improper sieving technique, moisture in samples affecting weight, and inaccurate weighing that can lead to unreliable results.

How often should ASTM C42 testing be performed on aggregate samples?

Testing frequency depends on project requirements and quality control protocols but is typically performed for each new source of aggregate or at regular intervals during production.

Are there any recent updates or revisions to ASTM C42?

As of October 2023, ASTM C42 has been periodically reviewed and updated to improve testing procedures, so it is recommended to consult the latest ASTM standards for the most current guidelines.

Can ASTM C42 test results be used for other construction materials besides concrete?

Yes, particle size analysis performed via ASTM C42 can also be relevant for mortar, asphalt, and other materials where aggregate grading impacts performance.

Additional Resources

Understanding ASTM C42: A Comprehensive Guide to Standard Test Method for Obtaining and Testing Drilled Cores of Concrete

When it comes to ensuring the quality, durability, and structural integrity of concrete in construction projects, standardized testing methods are essential. One such critical standard is ASTM C42, which provides a detailed procedure for obtaining and testing drilled cores of concrete. This test method plays a vital role in forensic analysis, quality assurance, and evaluating existing concrete structures. In this comprehensive guide, we'll explore the essentials of ASTM C42, its significance, the testing process, and practical applications.

What Is ASTM C42?

ASTM C42 is a standard developed by ASTM International that specifies the procedures for obtaining and testing drilled cores of concrete. It is primarily used in situations where existing concrete structures need to be evaluated, such as assessing strength, determining material properties, or investigating failures. The standard ensures that core samples are representative of the in-place concrete and that the testing process yields reliable, consistent data.

Importance and Applications of ASTM C42

Understanding the importance of ASTM C42 helps in appreciating its role in construction and maintenance:

- **Quality Control and Assurance:** Verifying that in-situ concrete meets specified strength and durability requirements.
- **Structural Evaluation:** Determining the integrity of existing structures, especially in repair or retrofit projects.
- **Forensic Investigations:** Analyzing concrete failures or deterioration by extracting core samples.
- **Material Characterization:** Assessing the properties of concrete used in a particular project to inform future designs or repairs.

Overview of the ASTM C42 Testing Process

The ASTM C42 procedure involves several key steps:

1. Preparation of the Test Site
2. Core Drilling
3. Handling and Labeling of Core Samples
4. Laboratory Testing of Cores
5. Data Analysis and Reporting

Let's delve into each of these stages in detail.

Preparing for Core Drilling

Before drilling, proper planning ensures the integrity of the sample and safety of personnel:

- Site Inspection: Identify the location for core extraction, avoiding areas with reinforcement, embedded electrical conduits, or other embedded items.
- Determining Core Size: Commonly, core diameters are 3 inches (75 mm) or 4 inches (100 mm). The selection depends on the purpose of testing and accessibility.
- Marking the Drilling Site: Clearly mark the area to be cored, ensuring the location is representative of the structure's condition.
- Safety Precautions: Use appropriate protective gear, and ensure the drill setup is secure to prevent accidents.

Core Drilling According to ASTM C42

Equipment Needed:

- Core drill with appropriate diamond-tipped core bits
- Vacuum or water cooling system
- Core catcher or core retention system
- Proper supports and fixtures for drilling

Drilling Procedure:

1. Align the Drill: Position the drill perpendicular to the surface to obtain a straight, representative core.
2. Cooling: Use water or vacuum cooling to prevent overheating and dust generation, maintaining the integrity of the sample.
3. Cutting the Core:
 - Drill slowly and steadily to prevent cracking.
 - Avoid applying excessive force.

- Stop drilling once the core is fully detached.
4. Extraction: Carefully remove the core from the hole, minimizing damage.
5. Coring Depth: Typically, cores are taken to a depth of at least 2 to 3 times the diameter to ensure representativeness, but minimum depths are specified in the standard.

Handling and Labeling of Core Samples

Proper handling ensures sample integrity:

- Label Each Core: Include information such as location, orientation, date, and identification number.
- Storage: Store cores in a dry, secure environment to prevent moisture loss or damage.
- Transportation: Minimize handling and avoid dropping or bending the cores.

Laboratory Testing of Cores

Once in the laboratory, cores are prepared for various tests:

- Visual Inspection: Check for cracks, voids, or other anomalies.
- Moisture Conditioning: Depending on the test, cores may be wetted or oven-dried.
- Density and Absorption Tests: Measure the density and water absorption to evaluate porosity and durability.
- Compressive Strength Testing:
 - Cores are capped or ground to ensure flat, parallel ends.
 - Compressive strength is measured using a hydraulic testing machine.
 - Results are compared to the specified or expected in-place strength.
- Other Tests: Depending on project requirements, cores can undergo sulfate resistance testing, permeability, or other property assessments.

Data Analysis and Reporting

The results from core testing are analyzed to determine if the concrete meets design specifications or to assess its condition:

- Calculating Strength: Average core strength and compare with specified strength.
- Interpreting Variability: Consider the standard deviation and potential reasons for variations.
- Reporting: Prepare comprehensive reports including:
 - Core sample details
 - Testing procedures
 - Results and interpretations

- Recommendations based on findings

Practical Considerations and Limitations

While ASTM C42 provides a standardized approach, practitioners should be aware of certain limitations:

- Core Size and Representativeness: Smaller cores may not fully capture the heterogeneity of the concrete.
- Potential for Damage: Core extraction can induce cracks or weaken the structure locally.
- Sample Quality: Broken or damaged cores may limit the accuracy of tests.
- Cost and Time: Core drilling and testing can be time-consuming and costly.

Tips for Successful Implementation

- Choose appropriate core locations that reflect the overall condition.
- Ensure proper drilling techniques to prevent damage.
- Handle cores carefully to preserve their integrity.
- Perform multiple tests for statistical confidence.
- Compare results with construction records and design specifications.

Conclusion

ASTM C42 serves as a cornerstone standard for obtaining and testing drilled cores of concrete, providing a reliable method to evaluate existing structures' strength and condition. Whether in quality control, forensic investigations, or structural assessments, adherence to ASTM C42 ensures that core sampling and testing are performed consistently and accurately. By understanding the detailed procedures and practical considerations outlined in this guide, engineers, inspectors, and contractors can confidently utilize core testing as a vital tool in their construction and maintenance workflows.

Final Thoughts

Incorporating ASTM C42 into your concrete evaluation protocols enhances the credibility and accuracy of your assessments. As construction materials and techniques evolve, maintaining rigorous testing standards like ASTM C42 helps safeguard structural safety, optimize repair strategies, and ensure long-term durability of concrete structures.

Astm C42

astm c42: Building Code Requirements for Structural Concrete (ACI 318-08) and Commentary ACI Committee 318, American Concrete Institute, 2008 The quality and testing of materials used in construction are covered by reference to the appropriate ASTM standard specifications. Welding of reinforcement is covered by reference to the appropriate AWS standard. Uses of the Code include adoption by reference in general building codes, and earlier editions have been widely used in this manner. The Code is written in a format that allows such reference without change to its language. Therefore, background details or suggestions for carrying out the requirements or intent of the Code portion cannot be included. The Commentary is provided for this purpose. Some of the considerations of the committee in developing the Code portion are discussed within the Commentary, with emphasis given to the explanation of new or revised provisions. Much of the research data referenced in preparing the Code is cited for the user desiring to study individual questions in greater detail. Other documents that provide suggestions for carrying out the requirements of the Code are also cited.

astm c42: An Introduction to Specifications for Cast-in-Place Concrete J. Paul Guyer, P.E., R.A., 2018-08-10 Introductory technical guidance for civil and structural engineers and construction managers interested in specifications for cast-in-place concrete construction.

astm c42: Design of Small Dams , 1987

astm c42: Roller-Compacted Concrete Dams CIGB ICOLD, 2020-12-14 ICOLD Bulletin 177 'Roller-Compacted Concrete Dams' presents the state-of-the-art on roller-compacted concrete technology for dams, incorporating the advances of the RCC technology for dams over the last 15 years since the previous Bulletin on the topic was released in 2003. Hence, the present ICOLD Bulletin 177 supersedes ICOLD Bulletin 126 ('Roller-compacted concrete dams - State of the art and case histories', published in 2003) and ICOLD Bulletin 75 ('Roller-Compacted Concrete for Gravity Dams' published in 1989). While roller-compacted concrete technology could have still been considered a new technology in 2003, it is now true to say that construction by roller-compaction has become the standard approach for large concrete gravity dams. This Bulletin addresses all aspects of the planning, design, construction and performance of RCC in dams. Mixture proportioning and quality control are discussed and a comprehensive listing of references is included. Many aspects of RCC in dams have become better understood since the publication of Bulletin No 126 and the present Bulletin contains less information on the particular approaches applied in different countries, but includes more comprehensive information particularly in relation to design, mixture proportioning and construction. With greater understanding, it has further been possible to highlight more definitively the requirements of successful RCC dams, as well as the pitfalls and difficulties that can be associated with RCC dam design and construction. Le Bulletin CIGB 177, intitulé « Barrages en Béton Compacté au Rouleau » présente les dernières avancées en matière de technologie du béton compacté au rouleau pour les barrages intégrant les progrès de la technologie BCR pour les barrages au cours des 15 dernières années, depuis que le dernier bulletin sur le sujet a été publié en 2003. Par conséquent, le bulletin 177 remplace le bulletin 126 (« Barrages en béton compacté au rouleau - Technique actuelle et exemples », publié en 2003) et le bulletin 75 (« Béton compacté au rouleau pour barrages-poids - Technique actuelle » publié en 1989). Alors que la technologie du BCR pourrait encore être considérée comme une nouvelle technologie en 2003, il est maintenant vrai de dire que la construction par le compactage par rouleaux est devenue l'approche standard pour les grands barrage-poids en béton. Ce bulletin aborde tous les aspects de la planification, de la conception, de la construction et de la performance du BCR dans les barrages. Le dosage du mélange et le contrôle de la qualité sont discutés et une liste exhaustive des références est incluse. De nombreux aspects du BCR dans les barrages sont mieux compris depuis la publication du Bulletin no 126. Le présent bulletin contient moins d'informations sur les approches particulières appliquées dans différents pays, mais comprend des

informations plus complètes notamment en ce qui concerne la conception, le dosage du mélange et la construction. Avec une plus grande compréhension, il a été possible de mettre en évidence les exigences des barrages en BCR réussis, ainsi que les pièges et les difficultés qui peuvent être associés à la conception et la construction du barrage en BCR.

astm c42: Index of Specifications and Standards , 2005

astm c42: The Code of Federal Regulations of the United States of America , 1998 The Code of Federal Regulations is the codification of the general and permanent rules published in the Federal Register by the executive departments and agencies of the Federal Government.

astm c42: Code of Federal Regulations, Title 29, Labor, Pt. 1926, Revised as of July 1 2011 Office of the Federal Register (U.S.) Staff, 2011-10-25

astm c42: Code of Federal Regulations , 1995

astm c42: Code of Federal Regulations, Title 29, Labor Office of the Federal Register (U.S.) Staff, 2012-10 The Code of Federal Regulations is a codification of the general and permanent rules published in the Federal Register by the Executive departments and agencies of the United States Federal Government.

astm c42: Labor (Parts 1911 - 1925) Code of Federal Regulations,

astm c42: 2017 CFR Annual Print Title 29 Labor Part 1926 Office of The Federal Register, 2017-07-01

astm c42: NBS Special Publication , 1968

astm c42: Construction Industry United States. Occupational Safety and Health Administration, 1991

astm c42: An Introduction to Specifications for Rehabilitation of Concrete for Professional Engineers J. Paul Guyer, P.E., R.A., 2024-07-20 Introductory technical guidance for professional engineers and construction managers interested in specifications for rehabilitation of concrete structures.

astm c42: Index of U.S. Nuclear Standards William J. Slattery, 1977

astm c42: ACI Manual of Concrete Inspection , 2008 This manual is intended to guide, assist, and instruct concrete inspectors and others engaged in concrete construction and testing, including field engineers, construction superintendents, supervisors, laboratory and field technicians, and workers. Designers may also find the manual to be a valuable reference by using the information to better adapt their designs to the realities of field construction. Because of the diverse possible uses of the manual and the varied backgrounds of the readers, it includes the reasoning behind the technical instructions. The field of concrete construction has expanded dramatically over the years to reflect the many advances that have taken place in the concrete industry. Although many of the fundamentals presented in previous editions of this manual remain relevant and technically correct, this eleventh edition incorporates new material to address these advances in technology

astm c42: Report , 1990

astm c42: Calcined Clays for Sustainable Concrete Karen Scrivener, Meenakshi Sharma, Franco Zunino, 2025-07-21 This book focuses on low-carbon sustainable cement production, performance, environmental efficiency, and other topics linked to calcined clays for sustainable concrete. It comprises select proceedings of the International Conference on Calcined Clays for Sustainable Concrete 2022, which was held at École Polytechnique Fédérale de Lausanne (EPFL)—Switzerland. The contents of this book focus on the influence of processing and clay mineralogy on the reactivity and rheology of calcined clay systems, Portland-calcined clay-limestone systems: hydration, durability, and performance, and calcined clay-alkali systems: hydration, durability, and performance, etc. This book can serve as a useful reference to researchers, academicians, and practitioners alike.

astm c42: An Introduction to Specifications for Marine Concrete for Professional Engineers J. Paul Guyer, P.E., R.A., 2024-07-26 Introductory technical guidance for Professional Engineers and construction managers interested in marine concrete construction.

Related to astm c42

ASTM C42 | Eng-Tips ASTM C 42 Some points to note for 4 inch slab. 1. Use pachometer to avoid rebar 2. Length to diameter ratio of between 1.9 to 1 and 2.1 to 1 is preferable. Correction values for
How do you determine the appropriate amount of concrete core That's probably a bit much, since you only need to verify an assumption. Given that, I would consider 6 to 9 cores, and possibly some consistency verification using either a

Low concrete strength | Eng-Tips Excessive air content, alone or coupled with other admixtures or cement types can cause this.

Would suggest the following course of investigative action:

Get all

Guide for Obtaining Cores and Interpreting Compressive - Eng I'm not sure where you are located, but in the US, the cores would be taken in accordance with ASTM C42 and the evaluation of the concrete would be done in accordance

ASTMC42 - Load Orientation - Earth retention engineering | Eng-Tips I am currently coring shotcrete test panels for a tieback shotcrete wall system. ASTM C42 requires you specify axial or lateral for the direction of load

Short height correction for unconfined compression test. I've been asked for a reference or formula for correcting unconfined compression tests on samples shorter than twice the diameter. I used to have that in my files, but now no

Re Concrete test hammer results | Eng-Tips These cores should be taken and tested in accordance with ASTM C42 "Standard Test Method for Obtaining and Testing Drilled Cores and Sawed Beams of Concrete". Most

28-day test failed - okay to wait for 56-day? | Eng-Tips The results of the 28-day tests aren't meeting the target compressive strength. We believe it's due to the strength retarding properties of fly ash in the mix. Assuming the 56-day

How to obtain beams for tensile testing of shotcrete | Eng-Tips One thing to note is that cores typically break at lower strengths than cylinders and this is accounted for in the testing procedures. There is the provision in ASTM C42 for sawing

minimum concrete strength | Eng-Tips The specifier of tests referenced in ASTM C42 shall be the licensed design professional. As always, we'll need to reference these codes often, so it's best to buy a copy of

ASTM C42 | Eng-Tips ASTM C 42 Some points to note for 4 inch slab. 1. Use pachometer to avoid rebar 2. Length to diameter ratio of between 1.9 to 1 and 2.1 to 1 is preferable. Correction values for
How do you determine the appropriate amount of concrete core That's probably a bit much, since you only need to verify an assumption. Given that, I would consider 6 to 9 cores, and possibly some consistency verification using either a

Low concrete strength | Eng-Tips Excessive air content, alone or coupled with other admixtures or cement types can cause this.

Would suggest the following course of investigative action:

Get all

Guide for Obtaining Cores and Interpreting Compressive - Eng I'm not sure where you are located, but in the US, the cores would be taken in accordance with ASTM C42 and the evaluation of the concrete would be done in accordance

ASTMC42 - Load Orientation - Earth retention engineering | Eng-Tips I am currently coring shotcrete test panels for a tieback shotcrete wall system. ASTM C42 requires you specify axial or lateral for the direction of load

Short height correction for unconfined compression test. I've been asked for a reference or formula for correcting unconfined compression tests on samples shorter than twice the diameter. I used to have that in my files, but now no

Re Concrete test hammer results | Eng-Tips These cores should be taken and tested in accordance with ASTM C42 "Standard Test Method for Obtaining and Testing Drilled Cores and

Sawed Beams of Concrete". Most

28-day test failed - okay to wait for 56-day? | Eng-Tips The results of the 28-day tests aren't meeting the target compressive strength. We believe it's due to the strength retarding properties of fly ash in the mix. Assuming the 56-day

How to obtain beams for tensile testing of shotcrete | Eng-Tips One thing to note is that cores typically break at lower strengths than cylinders and this is accounted for in the testing procedures. There is the provision in ASTM C42 for sawing

minimum concrete strength | Eng-Tips The specifier of tests referenced in ASTM C42 shall be the licensed design professional. As always, we'll need to reference these codes often, so it's best to buy a copy of

ASTM C42 | Eng-Tips ASTM C 42 Some points to note for 4 inch slab. 1. Use pachometer to avoid rebar 2. Length to diameter ratio of between 1.9 to 1 and 2.1 to 1 is preferable. Correction values for

How do you determine the appropriate amount of concrete core That's probably a bit much, since you only need to verify an assumption. Given that, I would consider 6 to 9 cores, and possibly some consistency verification using either a

Low concrete strength | Eng-Tips Excessive air content, alone or coupled with other admixtures or cement types can cause this.

Would suggest the following course of investigative action:

Get all

Guide for Obtaining Cores and Interpreting Compressive - Eng-Tips I'm not sure where you are located, but in the US, the cores would be taken in accordance with ASTM C42 and the evaluation of the concrete would be done in accordance

ASTM C42 - Load Orientation - Earth retention engineering | Eng-Tips I am currently coring shotcrete test panels for a tieback shotcrete wall system. ASTM C42 requires you specify axial or lateral for the direction of load

Short height correction for unconfined compression test. I've been asked for a reference or formula for correcting unconfined compression tests on samples shorter than twice the diameter. I used to have that in my files, but now no

Re Concrete test hammer results | Eng-Tips These cores should be taken and tested in accordance with ASTM C42 "Standard Test Method for Obtaining and Testing Drilled Cores and Sawed Beams of Concrete". Most

28-day test failed - okay to wait for 56-day? | Eng-Tips The results of the 28-day tests aren't meeting the target compressive strength. We believe it's due to the strength retarding properties of fly ash in the mix. Assuming the 56-day

How to obtain beams for tensile testing of shotcrete | Eng-Tips One thing to note is that cores typically break at lower strengths than cylinders and this is accounted for in the testing procedures. There is the provision in ASTM C42 for sawing

minimum concrete strength | Eng-Tips The specifier of tests referenced in ASTM C42 shall be the licensed design professional. As always, we'll need to reference these codes often, so it's best to buy a copy of

Related Articles

- [icivics judicial branch in a flash](#)
- [muscle diagram male](#)
- [accounting ratios cheat sheet](#)

[Back to Home](#)